

AMENDMENTS TO THE CLAIMS

Please cancel Claims 8, 17, 25, and 27 through 37 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 1, 13, 26, 38, 39, and 40, and add Claims 41 through 45 as follows:

1. (Currently Amended) A television signal receiving apparatus for receiving television signals including broadcast data signals, comprising:

receiver means for receiving the broadcast data signals;

output means for outputting the broadcast data signals, received by said receiver means, to a display device, wherein said display device displays an image including characters and/or pictures generated from the broadcast data signals;

communication means for communicating with an external device connected thereto; and

control means for controlling the image to be displayed on said display device so as to execute a script based on script information of the broadcast data signals in accordance with results of communication by said communication means.

2. (Original) An apparatus according to claim 1, wherein the data of the broadcast data signals includes display control data for use by said control means to modify the image displayed on said display device.

3. (Original) An apparatus according to claim 2, wherein the display control data comprises display layout information of the image to be displayed on said display device and script information for displaying the image on said display device.

4 . (Original) An apparatus according to claim 3, wherein the script information is associated with the results of communication, and
wherein said control means performs control to select the script information responsive to the results of communication and to perform a display process represented by the script information.

5. (Original) An apparatus according to claim 1, wherein said control means controls the output means so that a portion of the broadcast data signals is selectively output to said display device in response to the results of communication.

6. (Original) An apparatus according to claim 1, wherein the data of the broadcast data signals includes at least one of moving-picture data, still-picture data, audio data, character data, and control command data.

7 . (Original) An apparatus according to claim 6, wherein the character data is described in a markup language, and includes display layout information of the image displayed on said display device, and script information for displaying the image on said display device.

8. (Cancelled)

9. (Original) An apparatus according to claim 1, wherein said control means starts controlling said display device based on a notification from said communication means notifying that said external device has been connected thereto and has started communications.

10. (Original) An apparatus according to claim 1, wherein said control means controls said communication means to transmit a command querying the status of said external device, and controls said display device so that the displayed image is changed in response to data from said external device.

11. (Original) An apparatus according to claim 1, wherein said control means controls said display device so that the image displayed on said display device is changed in response to an event content of an event command received from said external device through the communication means.

12. (Original) An apparatus according to claim 1, wherein said external device comprises a printer device.

13. (Currently Amended) A television signal receiving apparatus for receiving television signals including broadcast data signals, comprising:

receiver means for receiving the broadcast data signals;

display means for displaying a plurality of images including an image relating to the broadcast data signals received from said receiver means;

print data output means for creating print data based on the broadcast data signals and for outputting the print data to a printer device; and

display control means for monitoring a status of said printer device and for changing a display content to be presented on said display means in accordance with the status of said printer device,

wherein said print data output means creates the print data in accordance with print layout information obtained from the broadcast data signals.

14. (Original) An apparatus according to claim 13, wherein data of broadcast data signals include at least one of moving-picture data, still-picture data, audio data, and character data.

15. (Original) An apparatus according to claim 14, wherein the character data is described in a markup language, and includes display layout information of an image to be displayed on said display device, print layout information of an image to be printed out on said printer device, and script information for displaying the image on said display device.

16. (Original) An apparatus according to claim 14, wherein said display control means monitors states of said printer device including, at least, one of a printing state, a print halted state, and an error state, and controls said display means so as to display at least one of the character data, the still-picture data, and the moving-picture data in response to the states.

17. (Cancelled)

18. (Original) A broadcast data receiving and reproducing apparatus for receiving broadcast data and for presenting a variety of displays of data including the broadcast data, comprising:

print data output means for forming print data based on the broadcast data and for outputting the print data to a printer device;

communication means for communication with said printer device;

control means for controlling said apparatus so as to execute a script based on script information of the broadcast data in accordance with results of communication by said communication means.

19. (Original) An apparatus according to claim 18, further comprising:

receiver means for receiving the broadcast data;

acquisition means responsive to the broadcast data for acquiring moving-picture data, audio data, and still-picture data multiplexed on a data broadcasting radio wave, character information described in a markup language, and markup text data including layout information and the script information;

storage means for storing the acquired data; and

display control means which generates display data based on the broadcast data and controls a display means so as to display the display data.

20. (Original) An apparatus according to claim 19, wherein the layout information comprises at least print layout information and display layout information, said print

data output means forms the print data based on the print layout information, and said display control means generates the display data based on the display layout information.

21. (Original) An apparatus according to claim 18, wherein said control means controls said apparatus so as to execute the script in response to a communication command reporting, output from said printer device to said communication means, based on a status of said printer device.

22. (Original) An apparatus according to claim 21, wherein said communication command reporting includes at least one of a print completed state, a print halted state, and an error state of the printer device.

23. (Original) An apparatus according to claim 18, wherein said control means start controlling of execution of the script in response to a notification from said communication means notifying that said printer device has been connected thereto and has started communication.

24. (Original) An apparatus according to claim 18, wherein the broadcast data includes information associating a status of said printer device with the script.

25. (Cancelled)

26. (Currently Amended) A television signal receiving method for receiving television signals including broadcast data signals, comprising the steps of:

- receiving the broadcast data signals;
- outputting the broadcast data signals received in the receiving step to a display device, wherein the display device displays an image including characters and/or pictures generated from the broadcast data signals;
- communicating with an external device connected thereto; and
- performing controlled modification of the image to be displayed on the display device so as to execute a script based on script information of the broadcast data signals in accordance with results of communication in the communication step.

27-37. (Cancelled)

38. (Currently Amended) A broadcast data receiving and reproducing system comprising a broadcast data receiving and reproducing apparatus for receiving broadcast data and for presenting a variety of displays of data including the broadcast data, and an external device with which the broadcast data receiving and reproducing apparatus communicates,

- wherein the broadcast data receiving and reproducing apparatus comprises:
 - receiver means for receiving data broadcasting radio waves,
 - acquisition means for acquiring at least one of moving-picture data, audio data, still-picture data, and character data multiplexed on the data broadcasting radio waves,
 - display means for displaying a variety of displays including the data acquired by the acquisition means,

communication means for communicating with the external device, and
display control means for controlling said display means to change the display
content on said display means so as to execute a script based on script information from the data
broadcasting radio waves based on results of communications with said external device.

39. (Currently Amended) A broadcast data receiving and reproducing system
comprising a broadcast data receiving and reproducing apparatus for receiving broadcast data and
for presenting a variety of displays of data including the broadcast data, and a printer device with
which the broadcast data receiving and reproducing apparatus communicates,

wherein the broadcast data receiving and reproducing apparatus comprises:

receiver means for receiving data broadcasting radio waves,

acquisition means for acquiring at least one of moving-picture data, audio data,
still-picture data, and character data multiplexed on the data broadcasting radio waves,

display means for displaying a variety of displays including the data acquired
by said acquisition means,

communication means for communicating with said printer device,

print data output means for forming print data based on stored data, and
outputting the print data to said printer device, and

display control means which monitors the status of said printer device, and
changes the display content on said display means based on a state of said printer device,

wherein said print data output means forms the print data in accordance with
print layout information obtained from the data broadcasting radio waves.

40. (Currently Amended) A television signal receiving apparatus for receiving broadcast television signals including data signals, representing an image including characters and/or pictures, comprising:

a receiver;

a display device in communication with said receiver by a signal outputter;

a communicator connected to an external device; and

a controller in communication with said communicator,

wherein said receiver receives the data signals, said outputter outputs the data signals, received by said receiver, to said display device, said display device displays an image including characters and/or pictures generated from the data signals, and said controller controls the image to be displayed on said display device so as to execute a script based on script information of the data signals in accordance with results of communication with said communicator.

41. (New) An apparatus according to claim 1, wherein said control means comprises (a) determining means for determining, in accordance with communication by said communication means, whether the external device has a printing function, and (b) means for controlling the image to be displayed on said display device in accordance with the determination by said determining means.

42. (New) A method according to claim 26, wherein said controlled modification step comprises (a) a step of determining, in accordance with communication of said communicating step, whether the external device has a printing function, and (b) a step of

modifying the image to be displayed on the display device in accordance with the determination by said determining step.

43. (New) A system according to claim 38, wherein said display control means comprises (a) determining means for determining, in accordance with communication by said communication means, whether the external device has a printing function, and (b) means for controlling said display means to change the display content on said display means in accordance with the determination by said determining means.

44. (New) An apparatus according to claim 40, wherein said controller comprises (a) a determining unit that determines, in accordance with communication by said communicator, whether the external device has a printing function, and (b) a controlling unit that controls the image to be displayed on said display device in accordance with the determination by said determining unit.

45. (New) A method for receiving broadcast data and for presenting a variety of displays of data including the broadcast data, said method comprising:

a print data output step of forming print data based on the broadcast data and for outputting the print data to a printer device;

a communication step of communicating with the printer device;

a control step of controlling an apparatus so as to execute a script based on script information of the broadcast data in accordance with results of communication by said communication step.